

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

Safety Data Sheet dated 7/11/2015, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: MAPEFLOOR PU 400 comp. B
CAS number: 37273-56-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Hardener for polyurethane-based adhesives.

1.3. Details of the supplier of the safety data sheet

Supplier:

Mapei d.o.o. , Novo mesto, Kocevarjeva 2, 8000 Novo mesto

Distribucijski center: Brezje pri Grosupljem 1c, SI-1290 Grosuplje, Slovenia

Competent person responsible for the safety data sheet:

sicurezza@mapei.it

1.4. Emergency telephone number

Mapei d.o.o. :Tel: + 386 (0)1 786 50 50

Fax: +386 (0)1 786 50 55

Poison Centre - Ospedale di Niguarda - Milan - Tel. +39/02/66101029

CORS – Center za obveščanje Republike Slovenije – Tel. 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

- ⚠ Warning, Acute Tox. 4, Harmful if inhaled.
- ⚠ Warning, Eye Irrit. 2, Causes serious eye irritation.
- ⚠ Danger, Resp. Sens. 1, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- ⚠ Warning, Skin Sens. 1, May cause an allergic skin reaction.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Symbols:



Danger

Hazard Statements:

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

H332 Harmful if inhaled.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

Precautionary Statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/...

Special Provisions:

None

Contents:

2,4-Diisocyanatotoluene-polypropylene glycol copolymer
4-methyl-m-phenylene diisocyanate

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 75% 2,4-Diisocyanatotoluene-polypropylene glycol copolymer

CAS: 37273-56-6

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.4.2/1 Skin Sens. 1 H317

>= 0.25% - < 0.49% 4-methyl-m-phenylene diisocyanate

REACH No.: 01-2119486974-18, CAS: 584-84-9, EC: 209-544-5

⚠ 3.6/2 Carc. 2 H351

⚠ 3.3/2 Eye Irrit. 2 H319

⚠ 3.8/3 STOT SE 3 H335

⚠ 3.2/2 Skin Irrit. 2 H315

⚠ 3.4.1/1 Resp. Sens. 1 H334

⚠ 3.4.2/1 Skin Sens. 1 H317

4.1/C3 Aquatic Chronic 3 H412

⚠ 3.1/1/Inhal Acute Tox. 1 H330

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

product must be rinsed immediately with plenty of running water and possibly with soap.
Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediately and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do NOT induce vomiting.

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

4.2. Most important symptoms and effects, both acute and delayed

The product is harmful following acute exposure to it and poses a serious health threat if inhaled.

If brought into contact with the eyes, the product causes considerable irritation which can last for over 24 hours.

If inhaled, the product may cause sensitisation of the airways, and if brought into contact with the skin it may cause sensitisation of the skin.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

None in particular.

Water.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

The original ingredients or unidentified toxic and/or irritant compounds may be present in the combustion fumes.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Limit leakages with earth or sand.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Rapidly recover the product, wearing protective clothing.

Suitable material for taking up: absorbing material, organic, sand

Wash with plenty of water.

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Fine dust may form explosive mixture with air. Keep away from open flames, heat and sparks.

Do not remove shrink film in hazardous locations (because of risk of static charging/discharge)

7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

4-methyl-m-phenylene diisocyanate - CAS: 584-84-9

NDS - LTE mg/m³: 0.007 mg/m³

NDSch - LTE mg/m³: 0.021 mg/m³

ACGIH - LTE mg/m³(8h): 0.005 ppm - STE mg/m³: 0.02 ppm - Notes: (), (SEN), (A4) - (Resp sens)

DNEL Exposure Limit Values

4-methyl-m-phenylene diisocyanate - CAS: 584-84-9

Worker Industry: 0.14 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 0.14 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 0.035 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 0.035 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

PNEC Exposure Limit Values

4-methyl-m-phenylene diisocyanate - CAS: 584-84-9

Target: Fresh Water - Value: 0.013 mg/l

Target: Marine water - Value: 0.00125 mg/l

8.2. Exposure controls

Eye protection:

Safety goggles.

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Suitable materials for safety gloves; EN 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Respiratory protection:

Use adequate protective respiratory equipment.

Personal Protective Equipment should comply with relevant CE standards (as EN 374 for gloves and EN 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Thermal Hazards:

None

Environmental exposure controls:

None

In case of insufficient ventilation use mask with AK2 filters (EN 141).

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:	liquid
Colour:	yellow
Odour:	typical
Odour threshold:	N.A.
pH:	n.a.
Melting point / freezing point:	N.A.
Initial boiling point and boiling range:	N.A.
Solid/gas flammability:	N.A.
Upper/lower flammability or explosive limits:	N.A.
Vapour density:	N.A.
Flash point:	ca.190 °C
Evaporation rate:	N.A.
Vapour pressure:	< 0.00001 kPa (23°C)
Relative density:	1,05 g/cm ³ (23°C)
Vapour density (air=1):	N.A.
Solubility in water:	insoluble, reagisce
Solubility in oil:	partly soluble
Viscosity:	7000 mPa.s (23°C)
Auto-ignition temperature:	N.A.
Explosion limits(by volume):	N.A.
Decomposition temperature:	N.A.
Partition coefficient (n-octanol/water):	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.

9.2. Other information

Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant properties	N.A.

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

SECTION 10: Stability and reactivity

- 10.1. Reactivity
Stable under normal conditions
- 10.2. Chemical stability
Stable under normal conditions
- 10.3. Possibility of hazardous reactions
It may generate flammable gases on contact with elementary metals (alkalis and alkaline earth, alloys in powder or vapours) and powerful reducing agents.
It may generate toxic gases on contact with oxidising mineral acids, and powerful oxidising agents.
It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.
- 10.4. Conditions to avoid
Stable under normal conditions.
- 10.5. Incompatible materials
None in particular.
- 10.6. Hazardous decomposition products
None.
It releases carbon dioxide in contact with water
It polymerises on heating

SECTION 11: Toxicological information

- 11.1. Information on toxicological effects
Route(s) of entry:
Ingestion: Yes
Inhalation: Yes
Contact: No
There is no toxicological data available on the mixture. Consider the individual concentration of each component to assess toxicological effects resulting from exposure to the mixture.
Toxicological information on main components of the mixture:
Toxicological information of the mixture:
N.A.
Toxicological information of the main substances found in the mixture:
2,4-Diisocyanatotoluene-polypropylene glycol copolymer - CAS: 37273-56-6
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat > 3.820 mg/l - Duration: 4h
4-methyl-m-phenylene diisocyanate - CAS: 584-84-9
a) acute toxicity:
Test: LD50 - Route: Oral - Species: Rat = 5110 mg/kg - Notes: male
Test: LD50 - Route: Oral - Species: Rat = 4130 mg/kg - Notes: female
Test: LD50 - Route: Skin - Species: Rabbit > 9400 mg/kg
Test: LC50 - Route: Inhalation - Species: Rat = 0.47 mg/l - Duration: 1h
Test: LC50 - Route: Inhalation - Species: Rat = 0.107 mg/l - Duration: 4h

Corrosive/Irritating Properties:
Eye:
The product can cause irritation by contact
Sensitizing Properties:
Frequent contact may cause sensitization.
Carcinogenic Effects:
No effects are known.
Mutagenic Effects:
No effects are known.
Teratogenic Effects:
No effects are known.
Additional Information:
Susceptibility to skin irritation and sensitization varies from person to person.

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

In a sensitized individual the allergic dermatitis may not appear until after several days or weeks of frequent and prolonged contact.

Therefore, even though the skin irritation potential is slight, skin contact should be avoided. Once sensitization has occurred, exposure of the skin to very small quantities of the material may cause erythema and edema.

For this reason, the contact with the skin should be avoided. Once sensitization has occurred, exposures to small amounts of material may cause erythema and edema locally.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

- a) acute toxicity
- b) skin corrosion/irritation
- c) serious eye damage/irritation
- d) respiratory or skin sensitisation
- e) germ cell mutagenicity
- f) carcinogenicity
- g) reproductive toxicity
- h) STOT-single exposure
- i) STOT-repeated exposure
- j) aspiration hazard

SECTION 12: Ecological information

12.1. Toxicity

Adopt good industrial practices, so that the product is not released into the environment.

Not available data on the mixture

Aquatic toxicity: the preparation is not to be considered toxic to the aquatic environment based on components.

LC50>100mg/l - aquatic species (calculated data following 1999/45/EC Directive).

4-methyl-m-phenylene diisocyanate - CAS: 584-84-9

a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia = 12.5 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish = 133 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

Not available data on the mixture

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. 91/156/EEC, 91/689/EEC, 94/62/EC and subsequent amendments.

Disposal of not hardened product (EC waste code) : 08 05 01

The suggested European waste code is just based on the composition of the product.

According to the specific process or application field a different waste code may be necessary.

SECTION 14: Transport information

9025896/1

Page n. 7 of 9

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

- 14.1. UN number
UN Number: ==
- 14.2. UN proper shipping name
N.A.
- 14.3. Transport hazard class(es)
Rail/Road(RID/ADR): no dangerous good
Air (ICAO/IATA): no dangerous good
Sea (IMO/IMDG): no dangerous good
N.A.
- 14.4. Packing group
N.A.
- 14.5. Environmental hazards
Marine pollutant: No
N.A.
- 14.6. Special precautions for user
N.A.
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
==

SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:
Restrictions related to the product:
Restriction 3
Restrictions related to the substances contained:
No restriction.
REACH Regulation (1907/2006) – All. XVII: N.A.
Legislative Decree no. 81 of the 9th of April 2008 Title XI "Dangerous substances - Chapter I - Protection against chemical agents"
Directive 2000/39/CE and s.m.i. (Professional threshold limit)
Legislative Decree no. 152 of the 3rd of April 2006 and subsequent modifications and additions. (Environmental regulations)
Directive 105/2003/CE (Seveso III): N.A.
ADR Agreement – IMDG Code – IATA Regulation
VOC (2004/42/EC) : N.A. g/l
- Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):
N.A.
- 15.2. Chemical safety assessment
No

SECTION 16: Other information

- Text of phrases referred to under heading 3:
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

Safety Data Sheet

MAPEFLOOR PU 400 comp. B

H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H315 Causes skin irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H412 Harmful to aquatic life with long lasting effects.
H330 Fatal if inhaled.

This safety data sheet has been completely updated in compliance to Regulation 2015/830/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

NIOSH - Registry of toxic effects of chemical substances
ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX'S - Dangerous properties of industrial materials
Insert here further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LTE: Long-term exposure.
PNEC: Predicted No Effect Concentration.
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE: Short-term exposure.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
OEL: Substance with a Union workplace exposure limit.
VLE: Threshold Limiting Value.
WGK: German Water Hazard Class.
TSCA: United States Toxic Substances Control Act Inventory
DSL: DSL - Canadian Domestic Substances List